

## SKY

189-0260010214660


SKY R RECESSED CEILING LUMINAIRE made of steel sheet, black, OptiLine 3x11 beam Wide beam (BS), light output direct, with converter, max. 300mA, dimmability: not dimmable, IP20 Six flame



## DRAWING



600 x 190 mm, ET 70 mm



## LIGHT DISTRIBUTION CURVE

## TECHNICAL DETAILS

|                       |                     |
|-----------------------|---------------------|
| System perform. [W]   | 53                  |
| Bulb type             | LED                 |
| Luminous flux [lm]    | 9100                |
| Current sec. [mA]     | 300                 |
| Colour temp. [K]      | 4000K               |
| CRI                   | >80                 |
| Optics                | OptiLine 3x11       |
| Converter             | with converter      |
| Dimming               | not dimmable        |
| Light output          | direct              |
| Beam angle [°]        | Breitstrahlend (BS) |
| Voltage [V]           | 220-240V 50/60Hz    |
| Material              | steel sheet         |
| Height [mm]           | 79                  |
| Recess depth [mm]     | 72                  |
| IP protection class   | IP20                |
| Voltage class         | protection cl. I    |
| Net weight [kg]       | 3,30                |
| Colour lamp           | black               |
| EAN-Number            | 9010870288737       |
| Lifetime [h]          | 60 000 L80 B10      |
| Ambient temperature   | 0° bis +35°         |
| Energy efficiency cl. | D                   |



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.