

SKY

189-0260010314550


SKY R RECESSED CEILING LUMINAIRE made of steel sheet, white, OptiLine 3x11 beam Double asymmetric (diam.) 2x25° and 1x60°, light output direct, with converter, max. 300mA, dimmability: not dimmable, IP20 Six flame



DRAWING



600 x 190 mm, ET 70 mm



LIGHT DISTRIBUTION CURVE

TECHNICAL DETAILS

| | |
|-----------------------|---|
| System perform. [W] | 53 |
| Bulb type | LED |
| Luminous flux [lm] | 9100 |
| Current sec. [mA] | 300 |
| Colour temp. [K] | 4000K |
| CRI | >80 |
| Optics | OptiLine 3x11 |
| Converter | with converter |
| Dimming | not dimmable |
| Light output | direct |
| Beam angle [°] | Doppelasymmetrisch (DA) 2x25° und 1x60° |
| Voltage [V] | 220-240V 50/60Hz |
| Material | steel sheet |
| Height [mm] | 79 |
| Recess depth [mm] | 72 |
| IP protection class | IP20 |
| Voltage class | protection cl. I |
| Net weight [kg] | 3,30 |
| Colour lamp | white |
| EAN-Number | 9010870288409 |
| Lifetime [h] | 60 000 L80 B10 |
| Ambient temperature | 0° bis +35° |
| Energy efficiency cl. | D |



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.