

SKY

189-0560010319550


SKY R RECESSED CEILING LUMINAIRE made of steel sheet, white, OptiLine 3x11 beam Double asymmetric (diam.) 2x25° and 1x60°, light output direct, with converter, max. 300mA, dimmability: not dimmable, IP20 Six flame



DRAWING



600 x 190 mm, ET 70 mm



LIGHT DISTRIBUTION CURVE

TECHNICAL DETAILS

System perform. [W]	53
Bulb type	LED
Luminous flux [lm]	9100
Current sec. [mA]	300
Colour temp. [K]	3000K
CRI	>80
Optics	OptiLine 3x11
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	Doppelasymmetrisch (DA) 2x25° und 1x60°
Voltage [V]	220-240V 50/60Hz
Material	steel sheet
Height [mm]	79
Recess depth [mm]	72
IP protection class	IP20
Voltage class	protection cl. I
Net weight [kg]	3,46
Colour lamp	white
EAN-Number	9010870509061
Lifetime [h]	60 000 L80 B10
Ambient temperature	0° bis +35°
Energy efficiency cl.	D



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.