

MAG

55-00004

MAG TRACK SET TRACK SPOTLIGHT SET WITH 3-PHASE ADAPTER made of aluminium, black, similar to RAL 9005, high quality glass lens beam 40°, light output direct, swiveling 350°, tilting 90°, with converter, max. 500mA, dimmability: phase section, IP20



DRAWING

TECHNICAL DETAILS

System perform. [W]	26W
Bulb type	LED
Luminous flux [lm]	2x1290lm
Current sec. [mA]	500mA
Colour temp. [K]	2700K
CRI	90
Optics	high quality glass lens
Converter	with converter
Dimming	phase section
Light output	direct
Beam angle [°]	40°
Voltage [V]	220-240V 50Hz
Material	aluminium
Length [mm]	1090
Height [mm]	135,5
Diameter [mm]	120
IP protection class	IP20
Voltage class	protection cl. I
Shock resistance	IK02
Net weight [kg]	2,41
Colour lamp	black
RAL	9005
EAN-Number	9010870567481
Lifetime [h]	50 000 L80 B10

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.