


RIDE

577-010013023060

RIDE SD WALL / CEILING LUMINAIRE made of die-cast aluminium, black, similar to RAL 9005, microprismatic PMMA cover for perfect anti-glare light output direct, with converter, max. 500mA, dimmability: not dimmable, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	10
Bulb type	LED
Luminous flux [lm]	780
Current sec. [mA]	500
Colour temp. [K]	2700K
CRI	>90
Optics	microprismatic cover
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Voltage [V]	220-240V 50/60Hz
Material	die-cast aluminium
Length [mm]	577
Width [mm]	35
Height [mm]	35
IP protection class	IP20
Voltage class	protection cl. I
Shock resistance	IK01
Net weight [kg]	1,65
Colour lamp	black
RAL	9005
EAN-Number	9008905693588
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	E
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.