

**TRAIL**

**610-1252031419040**

TRAIL LIGHT INSERT MOUNTING RAIL LIGHT INSERT made of aluminium, silver, similar to RAL 9006, linear optics beam 30°, light output direct, with converter, max. 600mA, dimmability: not dimmable, through wiring 7-polig, IP20




**DRAWING**



**TECHNICAL DETAILS**

System perform. [W]	92
Bulb type	LED
Luminous flux [lm]	12300
Current sec. [mA]	600
Colour temp. [K]	3000K
CRI	>80
Optics	high quality linear optics
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	30°
Voltage [V]	220-240V 50/60Hz
Through wiring	7-polig
Material	aluminium
Length [mm]	1696
Width [mm]	64
Height [mm]	16
IP protection class	IP20
Voltage class	protection cl. I
Shock resistance	IK06
Net weight [kg]	1,58
Color lamp	silver
RAL	9006
EAN-Number	9010506601558
Lifetime [h]	L90 B10 50 000
Energy efficiency cl.	C
No. of luminaires B16A	22

**LIGHT DISTRIBUTION CURVE**



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.