

TRAIL TRACK

666-200103031406b

TRAIL TRACK TRACK SPOTLIGHT WITH 3 PH ADAPTER made of aluminium, black, similar to RAL 9005, linear optics beam 60°, light output direct, UGR <22, swiveling 350°, with converter, max. 1050mA, dimmability: Smart bluetooth, adapter/ceiling base black, IP20




DRAWING



TECHNICAL DETAILS

System perform. [W]	40
Bulb type	LED
Luminous flux [lm]	5730
Current sec. [mA]	1050
Colour temp. [K]	4000K
CRI	>80
UGR	<22
Optics	high quality linear optics
Designer	INHOUSE
Converter	with converter
Light output	direct
Beam angle [°]	60°
Voltage [V]	220-240V 50/60Hz
Material	aluminium
Length [mm]	858
Width [mm]	64
Height [mm]	42
IP protection class	IP20
Voltage class	protection cl. II
Shock resistance	IK06
Net weight [kg]	1,03
Colour lamp	black
RAL	9005
Colour adapter/ceiling base	black
EAN-Number	9010506844481
Lifetime [h]	L80 B10 50 000
Energy efficiency cl.	C
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.