

BAFFEL

785-049510134906d

BAFFEL SPOT TRACK SPOTLIGHT WITH 3 PH ADAPTER black, similar to RAL 9005, decor black, high-efficiently vacuum deposited synthetic reflector beam 40°, light output direct, swiveling 350°, tilting 90°, with converter, max. 700mA, dimmability: DALI, cable transparent, adapter/ceiling base black, pendant length 1500mm, IP20



DRAWING

TECHNICAL DETAILS

System perform. [W]	2X14
Bulb type	LED
Luminous flux [lm]	2x 1510
Current sec. [mA]	700
Colour temp. [K]	3000K
CRI	PREMIUM>90
Optics	vacuum deposited synthetic reflector
Designer	INHOUSE
Converter	with converter
Light output	direct
Beam angle [°]	40°
Voltage [V]	220-240V 50/60Hz
Length [mm]	342
Width [mm]	52
Height [mm]	150
Pendant length [mm]	1500
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	1,56
Colour lamp	black
RAL	9005
Colour adapter/ceiling base	black
Colour decor	black
Electric wire	transparent
EAN-Number	9010870420144
Lifetime [h]	50 000 L80 B10
Energy efficiency cl.	E
No. of luminaires B16A	50

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.